

电容降压专用金属化聚丙烯膜交流电容器(X1类)

Metallized Polypropylene Film A.C. Capacitor For Capacitive Divider(Class X1)

■ 外形图Outline

■ 特点

专门设计使用在300~400vac电源串联的电
容降压电路场合，如电表；LED驱动模块等
金属化聚丙烯膜
自愈性能优异，能承受浪涌电压冲击
长期负载下优异的电容容量稳定性
优异的防潮性能
优异的阻燃性能


■ 符合ROHS.REACH等标准

■ Feature

Specially designed for using in a step-down series
circuit of a capacitor during 100 ~ 250vac, such as the meter,
LED drive module, etc.
Metallized polypropylene film
Excellent self-healing properties, be able to withstand the impact of the surge voltage
Excellent capacitance stability in long-term overload condition
Excellent moisture resistance
Excellent flame retardant properties

■ In accordance with ROHS and REACH

■ 技术参数Technical Parameters



引用标准 Reference Standard	GB/T14472(IEC60384-14)	安全认证 Certificates	UL,CUL,CQC,VDE,ENEC
电容器类别 Type	MKP/MPX X1类	气候条件 Climatic Conditions	40/110°C/56d
工作温度 Working Temperature	-40°C ~ +110°C	额定电压 Rated Voltage	440Vac, 50/60Hz
容量误差 Capacitance Tolerance	J- ± 5% K- ± 10% M- ± 20%	容量范围 Capacitance Range	0.01 μ F-1.0 μ F
耐电压 Proof Voltage	端子与端子: 4.3UR(VDC)5S 端子与外壳: 2000VAC 5S	Terminal to Terminal Terminal to Shell	无击穿或飞弧 No breakdown or electric arcing
损耗角 Dissipation Factor	≤0.0010 1KHZ		20°C; 1V测试电压 testing voltage
绝缘电阻或时间常数 Insulation resistance or time constant	CR ≤ 0.33 μ F IR ≥ 30000 M Ω CR > 0.33 μ F IR ≥ 10000 S (M Ω . μ F)		充电电压 100V 20°C Charging Voltage 充电 1min 测试后测得 And charging test 1min
耐湿负荷测试 Humidity Test	温度 85 ± 2°C Temperature 连续工作 30000 小时 Continuous working 施加电压: 380Vac Applied voltage		电容量衰减量: ΔC/C ≤ 10% Capacitance attenuation 损耗角衰减量: ΔTg δ ≤ 0.5% (1KHZ) Dissipation Factor attenuation 绝缘电阻值: IR ≥ 50% IR : IR ≥ 50%
注: 可根据客户使用定制容量产品, 具体参数依据承认书资料为准。 Note: Products capacitance can be customized, specific parameter according to documents.			

电容降压专用金属化聚丙烯膜交流电容器(X1类)

Metallized Polypropylene Film A.C. Capacitor For Capacitive Divider(Class X1)

■B43产品编码规则Production Coding Rules

一. 15位产品代码规定如下The coding rule of 15 digits of capacitor is as follows:

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----

二. 各部分组成内容Contents of each part

型号代码(第1~3位数)Type(Digits from 1~3th)

B43 电容降压专用金属化聚丙烯膜交流电容器(X1类)

B43 Metallized Polypropylene Film A.C. Capacitor For Capacitive Divider(Class X1)

标称容量(第4~6位数)Nominal Capacitance(Digit from 4~6th)

例如e.g.: 104 = $10 \times 10^4 \text{ pF} = 0.1 \mu\text{F}$

标容量误差代码(第7位数)Capacitance Tolerance Code(Digit 7th)

例如e.g.: J = $\pm 5\%$ K = $\pm 10\%$ M = $\pm 20\%$

额定电压(第8位数)Rated Voltage(Digit 8th)

例如e.g.: T---440Vac

塑壳代码(第9~10位数)Code for plastic case:(from 9~10th)



代码code	壳号case	代码code	壳号case	代码code	壳号case	代码code	壳号case	代码code	壳号case	代码code	壳号case
M1	M1	C1	C1	D5	D5	E5	E5	E1	E1	F8	F8
M2	M2	C2	C2	D7	D7	E6	E6	E2	E2	G1	TB5
M3	M3	C3	C3	D8	D8-3	E7	E7	E3	E3	G2	F14
M4	M4	CA	C5-1	DA	DA	F1	F1	E4	E4	G3	TB4
M5	M5	D1	D1	D3	D3	F2	F2	F4	F4	G4	TB23
M6	M6	D2	D2	D4	D4	F3	F3	F7	F7	G5	TB20

商标+塑壳颜色(第11位数)Mark+Plastic Case Color(Digit 11th)

代码code	商标+ 塑壳颜色 Mark+Plastic Case Color	代码code	商标+ 塑壳颜色 Mark+Plastic Case Color	代码code	商标+ 塑壳颜色 Mark+Plastic Case Color
R	SRD + 灰色激光打印 SRD + Grey, laser printing	B	SRD + 蓝色激光打印 SRD + Blue, laser printing	T	SRD + 黑色激光打印 SRD + Black, laser printing
S	SRD + 黄色无字激光打印 SRD + Yellow, no word laser printing				

内部识别码(第12~13位数)Internal Identification Code(from 12~13th)

外形加工识别码(第14~15位数)Outline Working Identification Code(from 14~15th)

说明: 标准引线长度为13mm		Note: The standard length of the lead is 13mm				
切引线标准长度(mm) The Cutting Length	3.0 ± 0.5	3.5 ± 0.5	4.0 ± 0.5	4.5 ± 0.5	5.0 ± 0.5	5.5 ± 0.5
直切脚加工图形 Straight-cut leads outline			弯切脚加工图形 Bend-cut leads outline			
						

电容降压专用金属化聚丙烯膜交流电容器(X1类)
Metallized Polypropylene Film A.C. Capacitor For Capacitive Divider(Class X1)

■成品尺寸表Finished Capacitor Size

成品编码 Part Number	容量 Cap	外形尺寸Dimension(mm)			
	μF	$W \pm 0.5$	$H \pm 0.5$	$T \pm 0.5$	$P \pm 0.5$
440Vac					
B43103KTC2-####	0.01	12.2	11	5	10
B43153KTC3-####	0.015	13	12	6	10
B43223KTC3-####	0.022	13	12	6	10
B43333KTC3-####	0.033	13	12	6	10
B43473KTD2-####	0.047	18	12	6	15
B43563KTD2-####	0.056	18	12	6	15
B43104KTD4-####	0.1	18	14.5	8.5	15
B43124KTD4-####	0.12	18	14.5	8.5	15
B43154KTD4-####	0.15	18	14.5	8.5	15
B43184KTDA-####	0.18	18	15.8	10	15
B43224KTD8-####	0.22	18	19	11	15
B43224KTE3-####	0.22	26.5	17	8.5	22.5
B43334KTE4-####	0.33	26.5	19	10	22.5
B43394KTE5-####	0.39	26.5	20	11	22.5
B43474KTE7-####	0.47	26.5	23	13	22.5
B43564KTF2-####	0.56	32	21.6	13	27.5
B43684KTF3-####	0.68	32	25	14	27.5
B43105KTF7-####	1	32	26	18	27.5